



5.906 Inch | 150 Millimeter x 9.843 Inch | 250
Millimeter x 3.15 Inch | 80 Millimeter SKF 23130
CCK/C3W33 Spherical Roller Bearings

Bearing No. 23130 CCK/C3W33

23130 CCK/C3W33 Bearing 2D drawings and 3D CAD
models

Category	Spherical Roller Bearings
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	15.414
EAN	7316576602702
Product Group	B04311
Internal Clearance	C3-Loose
Mounting Method	Adapter Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Tapered
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	AHX3130 (Specify bore)
Withdrawal Nut	KM33
Inch - Metric	Metric
Long Description	150MM Tapered Bore; 250MM Outside Diameter; 80MM Width; C3-Loose Clearance; Adapter Mount; Double Row of Spherical Roller Bearings; Steel Cage Material; Open Enclosure; Relubricatable; Adapter Part Nu



Luoyang SDZ Machinery Equipment Co., ...

Other Features	Order adapter or withdrawal sleeve or nut separately. Others may be available
Category	Spherical Roller Bearing
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer URL	http://www.skf.com
Weight / LBS	33.951
D	9.843 Inch 250 Millimeter
B	3.15 Inch 80 Millimeter
Adapter Part Number	SNW3130 H3130 HA3130 HE3130 (Specify bore) Inch H3130 (Specify bore) Millimeter
d	5.906 Inch 150 Millimeter
bore diameter:	150 mm
maximum rpm:	2600 RPM
outside diameter:	250 mm
operating temperature range:	Maximum of +390 ° F
overall width:	4.3800 in
cage material:	Steel
bore type:	Tapered 1:12
bearing material:	Steel
outer ring type:	Not Split
cage type:	Inner Ring Guided
internal clearance:	C3
precision rating:	Not Rated
closure type:	Open
finish/coating:	Uncoated
lubrication hole type:	Lubrication Groove & Hole



Luoyang SDZ Machinery Equipment Co., ...

outer ring width:	80 mm
dynamic load capacity:	830 kN
fillet radius:	2 mm
static load capacity:	1200 kN
series:	231